

# DILUENTE PER SMALTI RAPIDI

THINNER

code 5070712

## DESCRIPTION

Based on naphta derivatives and methyl acetate.  
For thinning of enamels, varnishes and synthetic rust inhibitors, quick-drying.  
It has a fast flash time and improves quick-drying, application and good flow.

## TECHNICAL SPECIFICATIONS

- Specific gravity: 0,80 kg/l
- Aspect: colorless liquid
- Flash point: 21-55 °C

## STORAGE

Maximum temperature for storage: +30 °C.  
Minimum temperature for storage: +5 °C.  
The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

## SAFETY RULES

This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments.  
highly flammable. / harmful by inhalation and if swallowed. / irritating to respiratory system.  
risk of serious damage to eyes. / toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. / harmful: may cause lung damage if swallowed. / keep out of the reach of children. / keep away from sources of ignition - no smoking. / handle and open container with care. / do not breathe vapour. / in case of contact with eyes, rinse immediately with plenty of water and seek medical advice. / do not empty into drains. / wear eye/face protection. / avoid release to the environment. refer to special instructions/safety data sheets. / if swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.  
contains: xylene (mixture of isomers), solvent naphta (petroleum), light arom  
The product must be transported, used and stored in accordance with the standards in force regarding hygiene and safety; after use, do not litter, let the residues dry out completely and treat them as special waste. For more information consult the safety data sheet.

*COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.*