

DILUENTE PER SPARTITRAFFICO

THINNER FOR TRAFFIC PAINT

code 5060605

DESCRIPTION

Mixing of organic solvents. It is the thinner for the traffic median paint SIGNALMARC series 010.

It has a fast flash time and improves quick-drying, application and good flow.

TECHNICAL SPECIFICATIONS

- Specific gravity: 0,96 kg/l
- Aspect: colorless liquid
- Flash point: 2-21 °C

STORAGE

Maximum temperature for storage: +30 °C.

Minimum temperature for storage: +5 °C.

The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

SAFETY RULES

This product is dangerous under 67/548/EEC and 1999/45/EC directives and subsequent amendments.

highly flammable. / irritating to eyes and skin. / harmful: danger of serious damage to health by prolonged exposure through inhalation. / possible risk of harm to the unborn child. / harmful: may cause lung damage if swallowed. / repeated exposure may cause skin dryness or cracking. / vapours may cause drowsiness and dizziness. / keep out of the reach of children. / keep away from sources of ignition - no smoking. / handle and open container with care. / do not breathe vapour. / avoid contact with eyes. / use only in well-ventilated areas. / if swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Contains: toluene

The product must be transported, used and stored in accordance with the standards in force regarding hygiene and safety; after use, do not litter, let the residues dry out completely and treat them as special waste. For more information consult the safety data sheet.

COLORIFICIO SAN MARCO guarantees that the information herein is provided to the best of its technical and scientific knowledge and based on its experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets. For further technical information call the technical service +39 041 4569322.